Tel: +44 (0)1626 833016
Fax: +44 (0)1626 833788 • Email: info@zenithdoors.co.uk
Western Units, Pottery Road, Bovey Tracey, Devon, TQ13 9JJ
www.zenithdoors.co.uk

Instant Roll Eco

Suitable for Indoor use. Maximum sizes: 4500mm wide x 4500mm high with light or moderate wind pressure

CURTAIN

Canvas:

Base of technical fabric of high tenacity polyester impregnated with tinted PVC.
Weight mass: 950 g/m2
Operating temperature from -30 to +70 º
Finish: Shiny lacquered on both sides.
Reaction to fire: Self-extinguishing M2.
Color: to be chosen among a wide array

Color	Red	Yellow	Green	Blue	Anthracite Grey	Window Grey	White
Similar to RAL	3002	1003	6026	Europe 95	7016	7040	9003
Fire Resistance	M2	M2	M2	M2	M2	M2	M2

Color	Ivory	Orange	Vermilion	Black	Brown		Grey
Similar to RAL	1014	2004	2002	9005	8016		9006
Fire Resistance	M3	M3	M3	M3	M3		M1

Cross beams for wind resistance:

In the standard configuration:

Material:

composite tubular profile fiberglass and polyester manufactured by pultrusion.

Resistance to wind load (according to UNE - EN 12424)

Standard: Class 0 (for indoor use with light air pressures)
Optional: Class 1 (for indoor use with light air pressures)

Socket: galvanised steel tube sized: 30 x 30 x 1,5.

.

Bottom bag to adjust the door canvas to the floor:

Material: Reinforced fabric of polyester impregnated with PVC.
Color: Yellow with black diagonal stripes.
Opening system with Velcro ® to reach the contact strip and the Radio-Band transmitter.
PVC crystal clear quality.
All the welds on the canvas are done by radio-frequencies, including the window welding.

STRUCTURE

General.

Self-supporting structure out of galvanized Steel. Grey Painted (RAL 7046) with a polyurethane color of 2 components
As an option, can be delivered painted in any RAL colour